

Tongue Shackle

Model TS



Summary Information

- Machined out of 17-4 PH Stainless Steel
- The Maximum Load Rating is based on a 4:1 ratio in Tension

| 50Thread | OAL IN | A | B | C | D | F | G | Max Load Rating |
|-------------|--------------|------|------|------|------|------|------|-----------------|
| 1/2-20UNF | 2.00 | 1.00 | 0.70 | 0.55 | 0.51 | 1.30 | 0.75 | 5000 lb |
| 5/8-18UNF | Call Factory | | | | | | | |
| 7/8-14UNF | Call Factory | | | | | | | |
| 3/4-16UNF | 3.25 | 1.50 | 1.31 | 0.94 | 0.76 | 2.07 | 1.25 | 10 k lb |
| 1-14UNF | 4.00 | 2.00 | 1.25 | 1.16 | 1.01 | 2.54 | 1.50 | 20 k lb |
| 1 1/4-12UNF | 7.00 | 3.00 | 2.62 | 2.03 | 1.76 | 4.22 | 1.50 | 50K lb |
| 1 1/2-12UNF | 7.00 | 3.00 | 2.62 | 2.03 | 1.76 | 4.22 | 2.50 | 50k lb |
| 2 1/2-12UN | 9.75 | 4.50 | 3.56 | 3.00 | 3.01 | 6.38 | 2.50 | 100k lb |

Other sizes and Metric threads are available. Contact the factory.

